



北京华腾凯经贸有限责任公司

北京市朝阳区松榆南路 54 号 3 层 邮编: 100122

Tel: (86 10) 8731 8925 Fax: (86 10) 8731 7378

Email: info@jingchem.com <http://www.jingchem.com.cn>

VT/HT标准贮罐

VT/HT STANDARD TANKS

型号 Model	水容积 Warm Water Volume (m³)	有效容积 Net. Liquid (m³)	高度/长度 Height / Length (m)	直径 Diameter (m)	正常蒸发量-氧 NER O₂ (%capacity/day)	最大允许工作压力 MAWP (MPa)
VT/HT 10	10.6	10	6.02	2.2	0.27	0.8~1.6
VT/HT 15	15.8	15	8.12		0.23	
VT/HT 20	21.1	20	10.2		0.21	
VT/HT 22	23.1	22	10.9			
VT/HT 25	26.4	25	9.6	2.5	0.2	
VT/HT 30	31.6	30	11			
VT/HT 33	34.7	33	12.2			
VT/HT 40	40	38	13.4	3	0.19	
VT/HT 50	50	47.5	11.3			
VT/HT 60	60	57	13.2			
VT/HT 80	80	76	13	3.6	0.18	
VT/HT 100	100	95	15.6			0.16

所有型号按需要提供不同压力和容积的特殊设计, 可以提供虹吸贮罐, 以上技术参数更新前不做更改通知。

Special design for pressure and volume are available on special request. Thermo siphon tanks are available for all models. Design and specification are subject to change without prior notice.

超大型低温贮罐

Super Large Tank

型号 Model	水容积 Warm Water Volume (m³)	有效容积 Net. Liquid (m³)	高度/长度 Height / Length (m)	直径 Diameter (m)	正常蒸发量-氧 NER O₂ (%capacity/day)	工作压力 Service Pressure (MPa)
VT/HT 150	150	147	23	3.6	0.15	0.2~3.5
VT/HT 200	200	196	23		0.13	
VT/HT 250	250	245	28	4.3	0.12	
VT/HT 300	300	294	33		0.11	
VT/HT 350	350	343	36			

所有型号按需要提供特殊设计, 以上技术参数更新前不做更改通知。

Special design are available for all models on special request. Design and specification are subject to change without prior notice.

VTC/HTC标准贮罐

VTC/HTC Standard Tank

型号 Model	水容积 Warm Water Volume (m³)	有效容积 Net. Liquid (m³)	高度/长度 Height / Length (m)	直径 Diameter (m)	正常蒸发量-二氧化碳 NER CO₂ (%capacity/day)	最大允许工作压力 MAWP (MPa)
VTC/HTC 10	10.6	10	6.02	2.2	0.7	2.2~2.5
VTC/HTC 15	15.8	15	8.12		0.5	
VTC/HTC 20	21.1	20	10.2		2.5	
VTC/HTC 30	31.6	30	11			
VTC/HTC 40	40	38	13.4	3.0	0.3	
VTC/HTC 50	50	47.5	11.3			
VTC/HTC 70	70	66.5	17			

所有型号按需要提供特殊设计, 以上技术参数更新前不做更改通知。

Special design is available for all models on special request. Design and specification are subject to change without prior notice.

VTN/HTN标准贮罐

VTN/HTN Standard Tank

型号 Model	水容积 Warm Water Volume (m³)	有效容积 Net. Liquid (m³)	高度/长度 Height / Length (m)	直径 Diameter (m)	正常蒸发量-天然气 NER LNG (%capacity/day)	最大允许工作压力 MAWP (MPa)
VTN/HTN 20	21.1	10	10.2	2.2	0.21	0.8~1.6
VTN/HTN 30	31.6	15	11	2.5	0.2	
VTN/HTN 40	40	20	13.4			
VTN/HTN 50	50	30	11.3	3.0	0.19	
VTN/HTN 60	60	38	13.2			
VTN/HTN 80	80	47.5	13			
VTN/HTN 100	100	66.5	15.6	0.16		

所有型号按需要提供其他压力和容积的特殊设计, 以上技术参数更新前不做更改通知。

Special design for pressure and volume are available on special request. Design and specification are subject to change without prior notice.

ISO 罐式集装箱

ISO Intermodal Containers

型号 Model	水容积 Warm Water Volume (m³)	设备重量 Tare weight (kg)	最大总质量 Max. Gross weight (kg)	长度 Length (mm)	宽度 Width (mm)	高度 Height (mm)	最大允许工作压力 MAWP (MPa)
CC-20-10	22.6	6750	34000	6058	2438	2591	0.2~3.7
CC-20-17		7800					
CC-20-24		8700					
CC-40-10	45	12000	12192				

所有型号按需要提供特殊设计, 以上技术参数更新前不做更改通知。

Special design are available for all models on special request. Design and specification are subject to change without prior notice.